

2-TANK

BUPI CLEANER® POWERTEC KLT PRO TWO-TANK SYSTEM WITH LIFTING DOOR

Clean production chains require periodic cleaning of the parts containers as well. Therefore, we have designed the KLT (small load carriers) series for this purpose.



SIEMENS



Read more at
www.bupicleaner.com/en/



TECHNICAL DATA

STANDARD SIZES WITHOUT ADDITIONAL EQUIPMENT

OVERALL DIMENSIONS APPROX.	SIZE 5
Width	2,720 mm
Depth	2,250 mm
Total height	2,950 mm
Total height with open lifting door	3,900 mm
Transfer height (upper edge grating)	880 mm
Useful dimensions L x W x H	1,220 x 1,000 x 1,200 mm
Load weight (payload)	200 kg
Total weight of the system	1,900 kg
POWER SUPPLY	
Electrical connection	56 kW
Max. current consumption	84 A
TECHNICAL PUMP DATA – CLEANING/RINSING	
Recirculation capacities	35.3/32.3 m ³ /h
Pump heads	520/420 kPa
Pump motors	7.5/5.5 kW
ELECTRICAL HEATING – CLEANING/RINSING	
Tank volumes	550/550 l
Electrical heating power values	18/18 kW

EQUIPMENT FEATURES:

- Media-contacting parts made of stainless steel
- Highly efficient Grundfos pumps
- Siemens S7-1200F safety control unit with 4-inch touch display
- Drilled full-jet nozzles
- Back flow filtration

RECOMMENDED ACCESSORIES:

- Vapour extraction unit
- Level control
- Three-phase oil separator
- Dosing unit
- Microfilter
- Hot-air dryer
- Feeder cart
- Inspection window, lighting
- Cascade control
- 7-inch touch display
- SLC cage and shelves

